



CRATE AXLES™

**KNOW WHAT YOU'RE
GETTING.
GET WHAT YOU KNOW.**



There are many imitations, but only one original.
The genuine Dana Crate Axle™ Program now
delivers the peace of mind that comes from
getting genuine Dana axles through our network
of authorized Dana Crate Axle™ specialists.





CRATE AXLES™

Spicer® Light Axle Ratings:

Model	Location	Ring Gear Size <i>inch</i>	Torque limit @ input <i>ft.-lbs.</i>	GAWR <i>lbs.</i>	GVW <i>lbs.</i>	GCW <i>lbs.</i>
Dana 30™	Front	7.30	1450	2800	5700	8000
Dana 44™	Rear	8.90	1930	3570	5700	8500
Dana 44™	Front	8.50	1930	3360	5700	8000
Dana 60™	Rear	9.75	2400	5760	8200	17100
Dana 60™	Front	10.10	2785	7350	16000	30000
Dana 70™	Rear	10.50	2600	8580	9900	18000
Dana 70™	Front	10.75	3450	8400	19500	26000
Dana 80™	Rear	11.25	3000	10100	14000	30000

Note: These ratings are general guidelines. Actual load rating and torque limit will vary by application and duty cycle.

Planned Ratios

Ratios:	30 Front	44 Rear	44 Front	60 Rear	60 Front	70 Rear	70 Front	80 Rear
3.73	X	A	X	A	X	X	X	X
4.10	X	A	X	A	X	X	X	X
4.56	X	X	X	X	X	X	X	X
4.88	X	X	X	X	X	X	X	X
5.13	X	X	X	X	X	X	X	X

A = Gear set is available. **X** = Gear set is planned for future release.

GAWR is Gross Axle Weight Rating. Maximum distributed weight an axle can support.

GVW is Gross Vehicle Weight Rating. Maximum allowable weight of vehicle when fully loaded.

GCW is Gross Combined (vehicle and trailer) Weight Rating. Maximum combined mass of vehicle and trailer when both are fully loaded.

Torque limit @ input (ft.-lbs.) is the maximum recommended driveline torque input into the axle flange/yoke at pinion.



For more information, please contact your local Spicer products sales representative or visit our website at www.crateaxle.com.

SPICER®



Dana Aftermarket Group

PO Box 321 Toledo, Ohio 43697-0321

Phone: 1.800.621.8084

www.spicerparts.com

Form # X5302-DAG

Copyright Dana Limited, 2012.

All rights reserved. Dana Limited.

Printed in U.S.A.

